



Capsule System



Tilting Plate



Power Boost



3 Way Pay

Cristallo Evo 400 Capsule

Description

Cristallo Evo 400 Capsule is based on the Cristallo platform, of which it maintains all the main characteristics; it is the latest Saeco technical development, using capsules, of the LB type or *Caffitaly System*, to brew coffee-based drinks. Inside the machine there are a capsule search/orientation rotor, a conveyor system and a dedicated brewing unit, for easy and effective capsule management. Thanks also to the 4 powder containers, the machine can brew a wide variety of drinks. Cristallo Evo 400 Capsule goes perfectly with the Artico S snack & food vending machine.

Cristallo Evo 400 Capsule: Heart of Coffee.

We are partnered by the best coffee roasters: Lavazza, for OCS, Caffitaly, with a proprietary capsule, and Covim, that adopted an LB-type capsule.

Accessories

- Independent water tank kit
- Timekeeper kit
- Mixer kit for tea spiral replacement with decaffeinated/barley
- Hot water solenoid valve kit
- Validator kit
- Eva-Dts kit
- Compartment lighting kit
- Lighting kit for upper and lower panels
- Keyboard lighting kit
- Customization kit

Main features

- Works with capsules of the LB type or *Caffitaly System*
- Loose capsule loading
- New boilers (300 cc)
- New silk-printed images for the upper and lower panels
- Easily customisable backlit front panels
- New backlit capacitive keyboard
- 4 instant product canisters
- Automatically dispenses cups (up to 400), sugar and stirrers
- Tilting main plate to allow direct access to all the internal components (Saeco Tilting Plate)
- Possibility to install 3 payment systems on the door at the same time (Saeco 3 Way Pay)
- Accepts the most commonly used parallel and serial MDB, BDV and Executive (possible Master and Slave configurations) payment systems
- Customisable settings
- Machine configuration with IeS software
- Soft-closing compartment door
- Integrated USB port

User interface

- Direct access 16-button keypad for beverage selection
- 4 preselection keys: +/-sugar, decaffeinated/barley and no-cup option
- Colour 3.5" graphic display

Technical data**Cristallo Evo 400 Capsule****Structural specifications**

Dimensions (w x h x d)	580 x 1700 x 670 mm
Weight	122 kg

Electrical specifications

Power supply	230V/50 Hz - 120V/60 Hz
Power consumption	1450 W

Water specifications

Boiler material	300 cc – brass
-----------------	----------------

Water connections

Water connection	3/4" (1–8 bar)
Water supply	standard: water supply - optional: independent water tank kit
Independent water tank	1 or 2 tanks of 15 l

Other specifications

Cups (h 70 mm)	400
Cups type ø	70 or 73 mm
Stirrers	400
Available stirrers	90 – 105 – 115 mm
Capsule container	1
Instant product container	4
Sugar container	1
Number of selections	16
Number of preselections	4
Disc mixer	2
Spiral mixer	1
Capsule brewing unit	yes

Canisters capacity

Capsules	310 LB-type or 300 <i>Caffitaly</i> system
Instant coffee	0.7 kg
Milk	2.5 kg
Chocolate	3 kg
The	3 kg
Sugar	3 kg

Technical specifications

- Containers and tanks in food-contact approved polypropylene
- Tilting main plate
- Water, coffee and cup-empty signal
- Capsule sensor
- Electronically controlled boiler temperature
- Exhauster to absorb internal moisture and additional steam exhauster for the dispensing area
- Removable cup-releasing device for easy cleaning and checking
- 60 W electromagnetic vibration pump
- Anti-overflow air-break device
- Simplified error reset
- Boiler safety valve
- General safety relay for 24 V components
- Thermal cut-outs on all devices supplied with line voltage
- CE, VDE and CSA approved



Artico S
+
Cristallo Evo 400 Capsule