



Capsule System



Tilting Plate



Power Boost



3 Way Pay

## Cristallo Evo 600 Capsule

### Description

Cristallo Evo 600 Capsule is based on the Cristallo platform, of which it maintains all the main characteristics; it is the latest Saeco technical development, using capsules, of the LB type or *Caffitaly System*, to brew coffee-based drinks. Inside the machine there are a capsule search/orientation rotor, a conveyor system and a dedicated brewing unit, for easy and effective capsule management. Thanks also to the 4 powder containers, the machine can brew a wide variety of drinks. Cristallo Evo 600 Capsule goes perfectly with the Artico L snack & food vending machine.

Cristallo Evo 600 Capsule: Heart of Coffee.

We are partnered by the best coffee roasters: Lavazza, for OCS, Caffitaly, with a proprietary capsule, and Covim, that adopted an LBtype capsule

### Accessories

- Independent water tank kit
- Timekeeper kit
- Mixer kit for tea spiral replacement with decaffeinated/barley
- Hot water solenoid valve kit
- Validator kit
- Eva-Dts kit
- Compartment lighting kit
- Lighting kit for upper and lower panels
- Keyboard lighting kit
- Customization kit

### Main features

- Works with capsules of the LB type or *Caffitaly System*
- Loose capsule loading
- New boilers (300 cc)
- New silk-printed images for the upper and lower panels
- Easily customisable backlit front panels
- New backlit capacitive keyboard
- 4 instant product canisters
- Automatically dispenses cups (up to 550), sugar and stirrers
- Tilting main plate to allow direct access to all the internal components (Saeco Tilting Plate)
- Possibility to install 3 payment systems on the door at the same time (Saeco 3 Way Pay)
- Accepts the most commonly used parallel and serial MDB, BDV and Executive (possible Master and Slave configurations) payment systems
- Customisable settings
- Machine configuration with IèS software
- Soft-closing compartment door
- Integrated USB port

### User interface

- Direct access 16-button keypad for beverage selection
- 4 preselection keys: +/-sugar, decaffeinated/barley and no-cup option
- Colour 3.5" graphic display

**Technical data****Cristallo Evo 600 Capsule****Structural specifications**

|                        |                     |
|------------------------|---------------------|
| Dimensions (w x h x d) | 580 x 1830 x 670 mm |
| Weight                 | 132 kg              |

**Electrical specifications**

|                   |                         |
|-------------------|-------------------------|
| Power supply      | 230V/50 Hz - 120V/60 Hz |
| Power consumption | 1450 W                  |

**Water specifications**

|                 |                |
|-----------------|----------------|
| Boiler material | brass (300 cc) |
|-----------------|----------------|

**Water connections**

|                        |   |
|------------------------|---|
| Water connection       | 3/4" (1-8 bar)  |
| Water supply           | standard: water supply - optional: independent water tank kit |
| Independent water tank | 1 or 2 tanks of 15 l  |

**Other specifications**

|                           |                   |
|---------------------------|-------------------|
| Cups (h 70 mm)            | 550               |
| Cups type ø               | 70 or 73 mm       |
| Stirrers                  | 550               |
| Available stirrers        | 90 – 105 – 115 mm |
| Capsule container         | 1                 |
| Instant product container | 4                 |
| Sugar container           | 1                 |
| Number of selections      | 16                |
| Number of preselections   | 4                 |
| Disc mixer                | 2                 |
| Spiral mixer              | 1                 |
| Capsule brewing unit      | yes               |

**Canisters capacity**

|                |  |
|----------------|--|
| Capsules       | 420 LB-type or 400 <i>Caffitaly</i> system |
| Instant coffee | 0.7 kg                                     |
| Milk           | 2.5 kg                                     |
| Chocolate      | 3 kg                                       |
| The            | 3 kg                                       |
| Sugar          | 4.5 kg                                     |

**Technical specifications**

- Containers and tanks in food-contact approved polypropylene
- Tilting main plate
- Water, coffee and cup-empty signal
- Capsule sensor
- Electronically controlled boiler temperature
- Exhauster to absorb internal moisture and additional steam exhauster for the dispensing area
- Removable cup-releasing device for easy cleaning and checking
- 60 W electromagnetic vibration pump
- Anti-overflow air-break device
- Simplified error reset
- Boiler safety valve
- General safety relay for 24 V components
- Thermal cut-outs on all devices supplied with line voltage
- CE, VDE and CSA approved



**Artico L**  
+  
**Cristallo Evo 600 Capsule**